

SRC 73B/1 BLUCHER 1965
OBSERVATION WELL NO. 3.

SW 1/4 4-27-35-2-W3

WELL COMPLETION LOG

240

WELL DEVELOPMENT

① BAILING

② PUMPING

SUBMERSIBLE SET 20 FEET
DISCHARGE IS 1 gpm.

4 1/2" O.D. STEEL 11 1/2' CASING.
SURFACE TO 250 FEET. CEMENTED BY
HALLIBURTON. 36 SKS CEMENT.
CEMENT RETURN TO SURFACE.

DRILLING & SAMPLE DESCRIPTION BY
P. MAIK, ELK POINT DRILLING.

4" ϕ LEAD PACKER WITH REDUCING
BUSHING 4" PACKER TO 3" CASING

8.3' - 3" ϕ WATER WELL CASING, CUT TO
DESIRED LENGTH WITH THREADED
END CONNECTIONS.

250

SAND, MEDIUM-COARSE GRAINED,
GREYISH, WELL ROUNDED, UNIFORM,
CALCAREOUS, UNOX.

SAND SAME AS ABOVE

SAND SAME AS ABOVE

4' - 4" ϕ STAINLESS STEEL 0.015 SLOT
JOHNSON WELL SCREEN, THREADED
END CONNECTIONS (M.F.)

SAND SAME AS ABOVE

260

BALL-TYPE UP TO CLOSE WASH DOWN
VALVE, 4" ϕ (M) THREAD TO SCREEN