

COMPLETION RECORD

6 5/8" CASING SET IN 9" HOLE TO 23'

7 7/8" HOLE FROM 23' TO 64.75'

CASING CEMENTED WITH 10 SACKS
CEMENT, SURFACE RETURN, NO PLUG
RUN. CEMENTED BY ELK POINT

5 5/8" HOLE DRILLED BELOW CASING TO 74.4'

RECORDER HOUSE GROUNDED IN PLACE Nov. 4, 1966
RECORDER INSTALLED Nov. 4, 1966

STATIC WATER LEVEL 22.1'

WELL DEVELOPED BY PUMPING
16 HOURS AT 10-12 GPM

MEDIUM SAND, PRIMARILY
0.008 - 0.012" SAND IS
SUBROUNDED TO SUBANGULAR
WITH APPROXIMATELY EQUAL
PORTIONS - QUARTZ, CHERT, & FELDSPAR;
GREENISH GRAINS (HORNEBLENDE?);
AND DARK GRAINS.

NOTE: DEPTH DATUM FROM TOP OF CASING

6 5/8" O.D. INSERT JOINT WATER WELL CASING
0.18" WALL THICKNESS TOP = GROUND + 0.6 FOOT

5 3/4" LEAD PACKER THREADED TO REDUCER BUSHING
REDUCER BUSHING

OVERALL ASSEMBLY LENGTH 12.9'
FROM TOP OF PACKER TO BOTTOM OF PLUG

EXTENSION OVERLAP 3.85'

3" EXTENSION COUPLER 7.95'

3" COUPLER

4.2' - 4" DIAMETER JOHNSON TELESCOPE SCREEN
STAINLESS STEEL, THREADED END CONNECTIONS
0010 SLOT

3" BASE PLUG

VERTICAL SCALE 1" = 2'
HORIZONTAL SCALE 1" = 16"

COMPILED BY: *J.H. Whiteaker*