

# COMPLETION RECORD

6 5/8" CASING SET IN 9" HOLE TO 23'

7 7/8" HOLE FROM 23' TO 47'

CASING CEMENTED WITH 8 SACKS  
CEMENT, SURFACE RETURN, NO PLUG RUN.  
CEMENTED BY ELK POINT DRILLING

5 3/8" HOLE DRILLED BELOW CASING TO 59.7'

MEDIUM SAND, PRIMARILY 0.008-0.012"  
SAND IS SURROUNDED TO SUBANGULAR  
WITH APPROXIMATELY EQUAL PORTIONS  
OF QUARTZ, CHERT, & FELDSPAR; GREENISH  
GRAINS (HORNEBLLENDE?); AND DARK GRAINS.

WELL DEVELOPED BY PUMPING  
16 HOURS AT ~6 GPM

RECORDER HOUSE GROUTED IN PLACE NOV. 7, 1966  
RECORDER INSTALLED NOV. 7, 1966

STATIC WATER LEVEL 6.9'

NOTE: DEPTH DATUM FROM TOP OF CASING

6 5/8" O.D. INSERT JOINT WATER WELL CASING  
0.18" WALL THICKNESS TOP = GROUND + 0.5 FOOT

5 3/4" LEAD PACKER THREADED TO REDUCER BUSHING  
OVERA

3" EXTENSION & COUPLER 2.85'

3" COUPLER

4.3' 4" DIAMETER JOHNSON TELESCOPE SCREEN  
STAINLESS STEEL, THREADED END CONNECTIONS  
0.007 SLOT

3" COUPLER

OVERALL ASSEMBLY LENGTH 15.95'  
FROM TOP OF PACKER TO BOTTOM OF PLATE

3" EXTENSION & COUPLER 8.25'

3" WELDED PLATE PLUG

VERTICAL SCALE 1" = 2'  
HORIZONTAL SCALE 1" = 16"

COMPILED BY: S.H. Whiteaker